

BROOKFIELD VISCOMETER BATH



TECHNICAL SPECIFICATIONS

Floor model with a stainless steel cold air cabinet and structure painted with anti-acid epoxidic products, fitted with 4 wheels with brake. Internal cabinet with turntable base at 4 rpm. Rack for 3 test tube and 3 balsa woodcell carrier. Cover with stop in aperture and automatic defrosting device, The temperature is controlled by digital thermoregulator PID fitted with a probe PT100 A, earth leakage circuit breaker, compressor CFC free refrigerant gases are used.

- **Temperature:** from ambient to -40°C
- **Stability:** $\pm 0.3^{\circ}\text{C}$
- **Power supply:** 230V $\pm 10\%$ 50Hz
- **Power:** 1600 W
- **Dimensions:** 82x88x160 cm
- **Weight:** 150 kg
- **Compliant to** ASTM D2983

Nordexp is a trade mark of
Nordtest s.r.l.
Via Livorno 11
15069 Serravalle Scrivia (AL)

Phone: +39014362422
E-mail: info@nordexp.com
Website: www.nordexp.com

ACCESSORIES :

ORIGINAL BROOKFIELD VISCOMETER

4B2 SPINDLE

TEST CELL, pack of 12 pcs

CELL STOPPER

BALSE WOOD TEST CELL CARRIER

SPINDLE CLIPS

THERMOMETER ASTM 123C IP 95C

THERMOMETER ASTM 124C IP 96C

THERMOMETER ASTM 125C IP 97C

**Nordexp is a trade mark of
Nordtest s.r.l.
Via Livorno 11
I 5069 Serravalle Scrivia (AL)**

**Phone: +39014362422
E-mail: info@nordexp.com
Website: www.nordexp.com**