



CLOUD AND POUR POINT REFRIGERATOR

TECHNICAL SPECIFICATIONS

Resistant structure painted with anti-acid epoxidic products, fitted with 4 wheels with brake. Glossy-black PVC cover with Small stand-by covers, aluminium blocks with holes for accommodate the graduated jars, equipped with a hole where the thermometer is placed. Temperature is controlled by Digital thermoregulator fitted with a probe PT100 A. Automatic Defrosting device under the cover, earth leakage circuit breaker, Independent compressors CFC free refrigerant gases are used.

conform to ASTM D97 IP 15 ISO 3016 ASTM D2500 IP 219 ISO 3015 ASTM D5853 IP 441

050061046 CLOUD AND POUR POINT REFRIGERATOR UP TO -69°C (4 POSITIONS)

Heating element controlled by an independent switch for a quick return to a ambient temperature.

- **Power supply:** 120 V 60 Hz
- **Power:** 1300W
- **Dimensions:** 60x70x100 cm
- **Weight:** 110 kg



Nordexp is a trade mark of
Nordtest s.r.l.
Via Livorno 11
15069 Serravalle Scrivia (AL)

Phone: +39014362422
E-mail: info@nordexp.com
Website: www.nordexp.com

**0500600117 CLOUD AND POUR POINT REFRIGERATOR UP TO
0° -18° -33° -51°C (4 POSITIONS)**

Heating element controlled by an independent switch for a quick return to a ambient temperature.

- **Power supply:** 120 V 60 Hz
- **Power:** 2900W
- **Dimensions:** 133x72x100 cm
- **Weight:** 208 kg



**0500600498 CLOUD AND POUR POINT REFRIGERATOR UP TO
0° -18° -33° (4 POSITIONS)**

Heating element controlled by an independent switch for a quick return to a ambient temperature.

- **Power supply:** 120 V 60 Hz
- **Power:** 2600W
- **Dimensions:** 104x72x100 cm
- **Weight:** 156 kg



Nordexp is a trade mark of
Nordtest s.r.l.
Via Livorno 11
15069 Serravalle Scrivia (AL)

Phone: +39014362422
E-mail: info@nordexp.com
Website: www.nordexp.com

0500600663 **CLOUD AND POUR POINT REFRIGERATOR 0° -18° -33° -51° -69°C (4 POSITIONS FOR EACH TEMPERATURE)**

Heating element controlled by an independent switch for a quick return to a ambient temperature.

- **Power supply:** 120 V 60 Hz
- **Power:** 3700W
- **Dimensions:** 180x72x100 cm
- **Weight:** 285 kg



ACCESSORIES:

FOR ASTM D97 D2500:

0500600118 TEST JAR SET

0500600077 THERMOMETER ASTM 5C IP 1C

0500600122 THERMOMETER ASTM 6C IP 2C

0500601048 THERMOMETER ASTM 61C IP63C

FOR ASTM D5853:

0500600118 TEST JAR SET

0500600387 SUPPORT FOR VESSEL ASTM D130 D5853

0500600377 PRESSURE VESSEL ASTM D130 D5853

0500600022 WATER/OIL BATH

0500600077 THERMOMETER ASTM 5C IP 1C

0500600122 THERMOMETER ASTM 6C IP 2C

0500601048 THERMOMETER ASTM 61C IP63C

Nordexp is a trade mark of
Nordtest s.r.l.
Via Livorno 11
15069 Serravalle Scrivia (AL)

Phone: +39014362422
E-mail: info@nordexp.com
Website: www.nordexp.com